WorkCentre 7228
shown with the Three Tray option.

WorkCentre 7235
shown with High-Capacity Feeder and Advanced Office Finisher options.

WorkCentre 7245
shown with High-Capacity Feeder and Professional Finisher options.

	WorkCentre® 7228	WorkCentre® 7235	WorkCentre® 7245
OUTPUT SPEED – printing and copying			
Black and White	Up to 28 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm), Up to 20 ipm 8.5 x 14 in. (216 x 356 mm), Up to 17 ipm 11 x 17 in. (A3/297 x 420 mm)	Up to 35 ipm 8.5 x 11 in. (A4/210 x 297 mm) Up to 21 ipm 8.5 x 14 in. (216 x 356 mm) Up to 17 ipm 11 x 17in. (A3/297 x 420 mm)	Up to 45 ipm 8.5 x 11 in. (A4/210 x 297 mm) Up to 27 ipm 8.5 x 14 in. (216 x 356 mm) Up to 22 ipm 11 x 17 in. (A3/297 x 420 mm)
Color	Up to 26 ipm 8.5 x 11in. (A4/210 x 297 mm) Up to 13 ipm 8.5 x 14 in. (216 x 356 mm) Up to 15 ipm 11 x 17 in. (A3/297 x 420 mm)	Up to 31 ipm 8.5 x 11in. (A4/210 x 297 mm) Up to 17 ipm 8.5 x 14 in. (216 x 356 mm) Up to 15 ipm 11 x 17 in. (A3/297 x 420 mm)	Up to 35 ipm 8.5 x 11 in. (A4/210 x 297 mm) Up to 21 ipm 8.5 x 14 in. (216 x 356 mm) Up to 17 ipm 11 x 17 in. (A3/297 x 420 mm)

Print Specifications

SYSTEM	
Memory	768 MB
System Disk	Minimum 40 GB
NETWORK PRINTING – Network Controller	
Processor	600 MHz
Printer Languages (auto sensing/switching)	Adobe Postscript® 3 TIFF PCL5 PDF 1.5 PCL 6 HP-GL, HP-GL2

Print Specifications

NETWORK PRINTING – resolution

PostScript: 600 x 600 dpi, 1200 x 1200 dpi
PCL emulation: 600 x 600, 1200 x 1200 dpi

NETWORK PRINTING – printing features

Print Calibration
Secure print
Delay print (specific time)
Sample set
Booklet creation
Cover selection
Paper selection by attribute
N-up
Poster mode
Saddle-stitch booklet making (requires Professional Finisher)
Hole Punch (requires Professional Finisher or Advanced Office Finisher)
V Folding (requires Professional Finisher)
Watermark
Fit to new paper size
Transparency interleave
Banner sheet enable/disable
Output tray selection
Image quality (High Speed, High Quality, High Resolution)
Draft mode
Annotation
Store and recall driver settings
Reduce/enlarge
Mirror image
Margins
Email Print
Bi-Directional
CMYK Color Balance

PRINT PROTOCOLS AND NETWORKS

Physical

Ethernet 100BaseT/10BaseT
USB printer port (optional)
Wireless Ethernet (IEEE 802.11b) via third-party adapters
Parallel Port (optional)

Continued

Print Specifications

PRINT PROTOCOLS AND NETWORKS (Continued)

Operating Systems

Microsoft® Windows® 95, 98, Me® (Millennium), NT® 4.0, 2000, XP®, Windows Server 2003
Citrix
Mac OS® 7.x, 9.x, 10.x
AIX 4.3.3
HP UX 11.0
Solaris 8, 9, 10
Linux® Red Hat 9®
Linux Yellow Dog 9®

Network Protocols

TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP
Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)
AppleTalk®: EtherTalk®
Microsoft Windows Networking over IP and NetBEUI

Administrative Protocols

DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet

Fonts

Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts
PCL: 84 scalable fonts, line printer bitmap font

Print Drivers

Environment	*PCL 6*	*PostScript*
Windows 95/98/Me	Bidirectional (enhanced*)	Bidirectional (enhanced*)
Windows NT 4.0	Bidirectional with user-selectable interface (standard** and enhanced)	Bidirectional with user-selectable interface (standard** and enhanced)
Windows 2000/XP Windows Server 2003/2003 64 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
Macintosh® System 9.x, OS X	N/A	Enhanced PPD file

Print Submission Tools

- Command prompt LPR tool for print submission
- TIFF/PDF/XPS: Supported in Windows 95/98/Me/NT 4.0/2000/XP Windows Server 2003
- Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)

**Enhanced: Xerox custom graphical user interface.*
***Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)*

	Print Specifications
DEVICE MANAGEMENT	
Management Support	SNMP Version 1 and SNMP Version 2c trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
CentreWare Network Services	Device Discovery wizard (available at www.xerox.com) Device Administration wizard (available at www.xerox.com) Font Management Utility
Xerox CentreWare Web	• A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
IP Filter	Allows administrator to control print access to device via IP address.
Xerox CentreWare® for Unicenter TNG®	• Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View • Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk
Xerox CentreWare® for Tivoli® Netware®	• Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView • Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet • Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)
Xerox CentreWare® for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
Xerox CentreWare® for HP® OpenView®	• Provides for the identification of Xerox N-Series printers and WorkCentre multifunction devices in the general discovery performed by HP OpenView • Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons • Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView

Continued

Print Specifications

DEVICE MANAGEMENT (Continued)

Xerox Device Types for SAP R/3 Environment	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): —Simplex or duplex printing —Finishing—single or dual stapling —Tray pull location from any tray —Print security via PIN ID capability at the WorkCentre
Xerox SAP R/3 Intelligent Barcode Utility (Optional) Purchase via www.font.net	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller —Tray status/contents —Consumables status
Xerox Barcode Pro PS (optional) Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.

CENTREWARE® INTERNET SERVICES – Integrated device Web Page

Device Status	Web server embedded on SMart network controller —Tray status/contents —Consumables status
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Windows XP, 2000/NT 4.0/Me/98/95: Netscape Navigator® 4.x and above, Microsoft Internet Explorer 4.x and above Macintosh 9.x/OS X: Netscape Navigator 6.x, Mac Safari, Firefox Linux: Netscape® 6.x

Scan Specifications

SCANNING (Optional)

Capability	Color Scanning, Greyscale, Black and White, Auto Color
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Input Speed	Scan at 50 ipm monochrome/45 ipm color (216 x 279 mm/A4 long edge feed)

Continued

Scan Specifications

SCANNING (Optional) (Continued)

Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (monochrome), 8 bit (greyscale), 24 bit (color)
Maximum Scan Area	11.7 x 17in. /297 x 432 mm
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/ Windows 2000/Windows Server 2003) LDAP
Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP
File Formats	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF with JPEG, G3 MH, MRC, G4 MMR, MRC, or JPEG compression JPEG High Compression PDF (optional) XPS Format
Document Management Fields	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard
Scan Feature Options	Mixed size originals Bound originals Edge erase Reduction enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression
Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Standard and Deluxe editions) Scan to Windows XP client SMB or FTP Scan to Mailbox

Continued

Scan Specifications

SCANNING (Optional) (Continued)

Scan to -PC Desktop Standard	— A desktop and server-based offering that provides document imaging, archiving, editing and organization tools — ScanSoft PaperPort – image viewing and file management software — ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software — Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
Scan to PC Desktop Deluxe	— A desktop and server based offering that provides document imaging, archiving, editing and organization tools — ScanSoft PaperPort Pro – image viewing and file management software — ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software — Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an Email inbox polling capability.

EMAIL (Included with Scanning Option)

Capability	Color scanning, Auto Color, Greyscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching
Network Protocol	SMTP, MIME encoded
Authentication	Device login with network user name and password Supports: Kerberos (Windows NT 4.0/UNIX,/Windows 2003 Server), SMB (Windows NT 4.0/ Windows 2000/Windows 2003 Server) LDAP Domino
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)

SCAN TO MAILBOX (Included with the Scanning Option)

Capability	Color, Auto Color, Black and White
Features	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Images that are stored in the mailbox can then be Emailed, sent via Fax, sent via IFax, routed to a PC, an FTP or SMB site.

THUMBNAIL PREVIEW (Optional)

Images that are stored in the mailbox can be viewed from the device.

Fax Specifications

NETWORK FAX SERVER INTEGRATION (Optional)

Fax Send Features	One- or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off
Fax Vendors	Multiple vendors, certified by the Xerox Business Partners Program For details, visit **www.xerox.com**

FAX (Optional) - Standard with One or Three line Fax option

	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
Speed/Compression	MH/G3, MMR/G4, JBig Super G3
Fax Send Features	Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan
Fax Receive Features	One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention
Fax Forward to Email	When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax.

Continued

Fax Specifications

FAX (Optional) - Standard with One or Three line option (Continued)	
Fax Reports	Activity report Dial directory Transmission confirmation Pending fax Mailbox
Fax Receive Mailboxes	Up to 200 password-protected mailboxes
Auto Dialing	Auto redial, Batch send
Single Line option	Total of 200 speed dials (single-line option) Up to 200 dial groups with up to 200 recipients per group (single line option)
Three Line option	1,000 speed dials (three line option) Up to 400 dial groups with up to 400 recipients per group (three line option)
INTERNET FAX (Optional) - Standard with One or Three line Fax option	
Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in color and black and white sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	11.7 x 17 in. /297 x 432 mm
Address Directory Access	Downloaded address list (comma-separated file format)
File Formats	TIFF-FX Profiles S, F with G3 MH, or G4 MMR
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (monochrome), 8 bit (greyscale)
Network Protocols	SMTP POP3
Compliance	ITU-T T.37 compliant

Copy Specifications

FIRST-IMAGE-OUT TIME – letter size, from platen to center tray			
Black and White	As fast as 5.7 Seconds	As fast as 5.7 Seconds	As fast as 4.8 Seconds
Color	As fast as 7.5 Seconds	As fast as 7.5 Seconds	As fast as 7.2 Seconds

COPYING	
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto color selection Poster mode Watermark Annotation Area Designation Full color Single/Dual color Copy calibration

Continued

Copy Specifications

COPYING (Continued)	
Special Features	Booklet creation Multi-up—2, 4 or 8 up Repeat image Transparency dividers Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job (enables special programming for different pages in one document—can be used for inserts, different paper sources,and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Hole Punch (requires Professional Finisher or Advanced Office Finisher) V-Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher) Stapling (single/dual/quad) quad requires Advanced Office Finisher or Professional Finisher ID Card Copy
Foreign Device Interface/ RS232 Port (optional)	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service

Device Specifications

PAPER HANDLING - Duplex Automatic Document Feeder	
Capacity	75 sheets (based on 80 gsm paper)
Speed	42 images per minute (Letter/A4 long edge feed (LEF))
Paper Sizes Sensed	Statement - 5.5 x 8.5 in. (A5/148 x 210 mm) long edge feed (LEF) or short edge feed (SEF) Letter - 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal - 8.5 x 14 in. (216 x 356 mm) SEF Ledger - 11 x 17 in. (A3/297 x 420 mm) SEF 8 x 10 in. (B5/182 x 257 mm) SEF
Weights	16 to 32 lb bond/38 to 128 gsm

Device Specifications

PAPER HANDLING - Bypass Tray	
Capacity*	100 sheets
Sizes	4.13 x 5.83 in. (A6/105 x 148 mm) to 12 x 19 in. (SRA3/320 x 450 mm)
Weights	16 lb bond to 80 lb Cover/60 to 220 gsm
Types	Same as front-loading trays plus label stock and envelopes
PAPER HANDLING - Front-Loading Paper Tray (Standard)	
Capacity*	520 sheets
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	17 to 80 lb Cover/55 to 220 gsm
Types	Plain paper Bond Preprinted forms Recycled paper Transparencies Heavyweight
PAPER HANDLING - Input Tray Options - Three Tray Option (Tray One and Two plus Two Tray Module)	
Tray 2 - Tray 4	520 sheets
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	17 to 80 lb Cover/55 to 220 gsm
Types	Plain paper Bond Preprinted forms Recycled paper Transparencies Heavyweight
Total Capacity*	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)

Continued

**Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.*

Device Specifications

PAPER HANDLING - Input Tray Options - High-Capacity Feeder Option	
Tray 2	520 sheets
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Tray 3 - Tray 4	2,000 sheets
Sizes	8.5 x 11 in., B5, A4
Weights	17 to 80 lb Cover/64 to 220 gsm
Types	Plain paper Bond Preprinted forms Recycled paper Transparencies Heavyweight
Total Capacity*	3,140 sheets (Includes Tray 1, Tray 2, Bypass Tray and High Capacity Feeder)
OUTPUT - Center Stacking Tray	
Stacking Tray	400 sheets (200 sheets with finisher option)
Sizes	4.13 x 5.83 in. (A6/105 x 148 mm) to 12 x 19 in./320 x 483 mm
OUTPUT - Convenience Stapler Option	
Capacity*	Up to 50 sheets (5,000 staples per cartridge)
OUTPUT - Office Finisher Option	
Stacking Tray	1,000 sheets
Sizes	8 x 10 in./B5 to 11 x 17 in./A3
Weights	17 to 28 lb bond/64 to 105 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum) – 20 lb/80 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

Continued

**Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.*

	Device Specifications
OUTPUT - Advanced Finisher Option	
Top Tray	500 sheets
Stacking Stapling Tray	3,000 sheets
Sizes	8 x 10 in./B5 to 11 x 17 in./A3
Weights	17 to 80 lb Cover/60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum) – 24 lb bond/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	3- or 2/4-hole punch
OUTPUT - Professional Finisher Option	
Top Tray	500 sheets
Stacking Stapling Tray	1,500 sheets
Sizes	8 x 10 in./B5 to 11 x 17 in./A3
Weights	17 to 110 lb index/60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 60 lb Cover/169 gsm plus fourteen 24 lb bond/90 gsm sheets) V-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
Hole Punch	3- or 2/4-hole punch
SECURITY	
Capability	Secure Print, timed auto delete secure print, NDS Authentication over IP, LDAP/Kerberos/SMD
Optional Security Kit Capability	Secure Watermark, Password Protected PDF, Encrypted Disk, Audit Log and Encrypted Scan to Email. Hard disk overwrite immediate or on demand. Secure Web Page via SSL.

	Device Specifications
ACCOUNTING	
Accounting with Third-Party Server Applications (optional)	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax
Internal Auditron	Tracks black and color copy and print usage, supports up to 1,000 user accounts Note: Option to upload/download account and usage data via direct connection using Windows-based software. Limits user to black-only copy and print
Accounting Control	Job based accounting Third-party integration
ACCOUNTING OPTIONS - Xerox Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 750 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.

	WorkCentre® 7228	WorkCentre® 7235	WorkCentre® 7245
MONTHLY DUTY CYCLE			
	80,000	105,000	135,000
BASIC CONFIGURATIONS**			
	Network Multifunction System with network controller and stand Notes: Platen cover, Duplex Automatic Document Feeder is available with all configurations		
ACCESSORIES			
	Office Finisher Advanced Office Finisher Professional Finisher One-line fax option Three-line fax option Foreign Device Interface Network Accounting Enablement Network Scanning With Email Fax Server PDF/XPS Compression Kit		

Continued

**Features, configurations and options may vary by location.*

Device Specifications

ACCESSORIES

Thumbnail preview
Internet Fax
Image Disk Overwrite Security
Scan to PC Desktop Client Software (Standard or Deluxe)
USB Port Printing
High Capacity Feeder
3 Tray option

ELECTRICAL REQUIREMENTS

220–240 V Nominal, 50/60 Hz, 10A

POWER CONSUMPTION

Running	< 1012 watts
Standby	< 200 watts
Low-Power Mode	< 80 watts
Sleep Mode	< 10 watts
Warm Up	45 seconds (maximum)
Low-Power Recovery	30 seconds (maximum)

POWER CONSUMPTION

Required Temperature Range	50° to 82° F (10° to 28° C)
Required Relative Humidity	15% to 85%
Noise Emission	28 dB(A) standby 56 dB(A) running 61 dB(A) impulse
Heat Emission	3441 BTU/Hr running 683 BTU/Hr standby

**Features, configurations and options may vary by location.*

Device Specifications

DIMENSIONS AND WEIGHT	*width*	*depth*	*height*	*weight*
Fully Configured	53 in./1,346 mm	25 in./635 mm	43.9 in./1,115 mm	457 lbs/257 kg
	71.5 in./1,816 mm	48 in. /1,219 mm	78 in. /1,981 mm	

CERTIFICATIONS

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)
89/336/EEC (Europe)
UL Listed (UL60950-1, First Edition)
CB Certified (IEC 60950-1/EN 60950-1)
73/23/EEC (Europe)
Novell Tested and Approved
Windows Hardware Quality Labs

SUPPLIES	*Description*	*Order Number*	
Toner Cartridges	Black	006R01280	
	Cyan	006R01281	
	Magenta	006R01282	
	Yellow	006R01283	
Staple Refills	For Office Finisher	8R12915	
	For Advanced Finisher	8R12941	Used on Advanced and Professional Finisher plus Convenience Stapler 3 refills at 5,000 each
	For Professional Finisher	8R12925	Used on Professional Finisher (Booklet Function) 4 refills at 5,000 each
Staple Cartridges	For Advanced and Professional Finishers	8R12964	Used on Advanced and Profession al Finisher plus Convenience Stapler (1 cartridge for repair)

SMART KITS

Smart Kit™ Drum Cartridge	13R00624	
Smart Kit™ Waste Cartridge	008R12903	
Smart Kit™ Fuser Module	008R13028	

SMART eSOLUTIONS

Meter Assistant	Via proxy
Supplies Assistant	Via proxy

XEROX BUSINESS PARTNER

© 2006 Xerox Corporation. All rights reserved. XEROX®, WorkCentre®, CentreWare® and Copier Assistant are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product information and/or specifications are subject to change without notice. 03/07 610P725960D W72SS-01UE